

## Automatic transmission fluid ISO L-HA

# ATF<sup>®</sup> A SUFIX A

ATF<sup>®</sup> A SUFIX A is transmission fluid manufactured from carefully selected solvent neutral oils and additives that provide its high thermal and oxidation stability, high shear stability, excellent corrosion prevention, high viscosity index, excellent low temperature properties, extraordinary ability of releasing air without foam creation, excellent antiwear properties as well as precisely defined friction characteristics.

### ADVANTAGES

- Excellent antiwear protection;
- Excellent thermal and oxidation stability;
- Neutral towards standard seals.

### QUALITY LEVEL

ISO 6743-4

GM ATF Type A Suffix A

### APPLICATION

ATF<sup>®</sup> A SUFIX A is oil primarily recommended for the lubrication of General Motors automatic transmission systems.

It is recommended for the lubrication of automatic transmission and hydraulic gears and servo units. This oil is also used for hydraulic steering wheels, hydraulic couplings, hydraulic transmission systems for servo steering wheels of heavy motor vehicles, for torque converters in motor vehicles, agricultural and construction machines where the oils GM ATF type A suffix A are prescribed.

### TYPICAL CHARACTERISTICS

	TYPICAL VALUE	METHOD
Density at 15°C, g/ml	0,87	SRPS EN ISO 3675
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	37	SRPS ISO 3104
Kinematic viscosity at 100°C, mm <sup>2</sup> /s	7,0	SRPS ISO 3104
Viscosity index	150	SRPS ISO 2909
Flash point, °C	220	SRPS EN ISO 2592
Pour point, °C	-42	SRPS ISO 3016
Cu corrosion, 3h/150°C, degree	1	SRPS EN ISO 2160
Brookfield viscosity at -23,3°C, mPas	4500	ASTM D 2983
Brookfield viscosity at -40,0°C, mPas	64000	ASTM D 2983



#### STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

#### PACKING

Drums 180kg, cans 20L, 10L, 1L and 0,5L.

---

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia

Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008

[www.fam.rs](http://www.fam.rs)