

## Circulating oils

### ISO L-HL

# FAMCIRKOL 3

FAMCIRKOL 3 oil is made of quality solvent neutral base oils of paraffin base, with good oxidation stability and high viscosity index. Additives provide to these oils high level of protection of metallic components from corrosion and from premature wear and good separation of water and air.

#### QUALITY LEVEL

ISO 6743-4

#### APPLICATION

FAMCIRKOL 3 is used for the lubrication of lightly loaded high speed rolling and sliding bearings of spindles and gear transmission. It can also be applied in circulation systems lubrication in grinder spindles, high-speed machine tools, centrifuges, light textile machines, spinning machines etc. This oil has the property to separate air easily, it does not foam and it separates water easily.

#### TYPICAL CHARACTERISTICS

|             | Kinematic viscosity<br>(mm <sup>2</sup> /s) na |       | Flash point<br>°C | Density at 15°C |
|-------------|------------------------------------------------|-------|-------------------|-----------------|
|             | 40°C                                           | 100°C |                   |                 |
| FAMCIRKOL 3 | 3.02                                           | -     | 120               | 0.8300          |

#### STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

#### PACKING

Drums 180 kg and cans of 20L.

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.