

Engine oil for two-stroke engines ISO L-EGB

FAMDUOTAKT[®] EXTRA N

FAMDUOTAKT[®] EXTRA N is optimally additivated mineral oil for two-stroke gasoline engines.

ADVANTAGES

- High oxidation and thermal stability;
- Non-flammable, it does not contain easily flammable solvents;
- Good performances in application.

QUALITY LEVEL

ISO 6743-15

API TB

JASO FB

APPLICATION

FAMDUOTAKT[®] EXTRA N is mineral oil for the lubrication of gasoline two-stroke engines. It is recommended for the lubrication of air-cooled small two-stroke motorcycle engines, chainsaws, lawn mowers, etc.

FAMDUOTAKT[®] EXTRA N can be mixed with all types of gasoline (unleaded, 86 octane, 93 octane, 98 octane) as per manufacturer recommendation.

TYPICAL CHARACTERISTICS

	TYPICAL VALUE	METHOD
Density at 15°C, g/cm ³	0,88	SRPS EN ISO 3675
Kinematic viscosity at 40°C, mm ² /s	73	SRPS ISO 3104
Kinematic viscosity at 100°C, mm ² /s	9,5	SRPS ISO 3104
Flash point, °C	215	SRPS EN ISO 2592
Pour point, °C	-15	SRPS ISO 3016
Cu corrosion, 3h/121°C, degree	1	SRPS EN ISO 2160

STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

PACKING

Drums 180kg, plastic cans of 0,5L, 1L and 5L.

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.

December, 2016