

## Oil for tractor engine, transmission and hydraulics ISO L-E/C/H

# FENIX<sup>®</sup> SUPER TRAKTOL SAE 15W-40

FENIX<sup>®</sup> SUPER TRAKTOL SAE 15W-40 is high quality multipurpose tractor oil STOU (Super Tractor Oil Universal), specially formulated and developed for efficient lubrication of mechanical parts, couplings, including those with sophisticated design on tractors with modern design.

### ADVANTAGES

- Engine oil with high detergent and dispersing properties and good thermal and oxidation stability, good antiwear and anticorrosion protection;
- Transmission oil with capability of enduring high pressures, also suitable for the lubrication of hypoid gears;
- Hydraulic oil that meets the requirements of hydraulic systems in high and low temperatures;
- It is used for the lubrication of wet brakes and gears thus providing safe braking and good operation of reducer components.

### QUALITY LEVEL

API CF-4/CD/CE/SF/SE	Massey Ferguson CMS M1139/M1144/M1145
ACEA E2	FORD M2C 159B
MB 227.1/ 228.1	API GL-4
MIL-L-2104D	Allison C-4
John Deere JDM J27	ZF TE-ML 06B, 06D, 07B
	Caterpillar TO-2

### APPLICATION

FENIX<sup>®</sup> SUPER TRAKTOL SAE 15W-40 is high quality universal oil meeting requirements for the lubrication of diesel engines with and without turbocharging, gearboxes, transmissions, differentials and gears, hydraulic systems and wet brakes of tractors.

FENIX<sup>®</sup> SUPER TRAKTOL SAE 15W-40 can be used as engine oil for transportation vehicles and other equipment thus limiting exclusively to its characteristics of being multifunctional oil.

### TYPICAL CHARACTERISTICS

	TYPICAL VALUE	METHOD
Density at 15°C, g/ml	0,88	SRPS EN ISO 3675
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	111	SRPS ISO 3104
Kinematic viscosity at 100°C, mm <sup>2</sup> /s	14.4	SRPS ISO 3104
Viscosity index	130	SRPS ISO 2909
Flash point, °C	220	SRPS EN ISO 2592
Pour point, °C	-33	SRPS ISO 3016
Cu corrosion, 3h/150°C, degree	1	SRPS EN ISO 2160



#### STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

#### PACKING

Drums 180kg and containers of 10L and 5L.

---

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.



December, 2016

FABRIKA MAZIVA FAM • Jug Bogdanova 42 • 37000 Kruševac • Serbia

Tel. ++381 37 422078; 423261 • Fax. ++ 381 37 426241; 424008

[www.fam.rs](http://www.fam.rs)