

Engine oils

ISO L-E

FENIX[®] SUPERIOR PLUS SAE 10W-40

High quality multigrade semi-synthetic mineral SHPD (Super High Performance Diesel) engine oil prescribed by diesel engine manufacturers. Oil provides cylinder anti-wear protection and excellent detergent properties. With a suitable combination of base oils it provides long oil change interval.

ADVANTAGES

- High alkaline reserve level;
- Excellent shear stability;
- Exceptional thermal and oxidation stability;
- Improved protection against wear and corrosion of engine parts;
- Easy engine start and application at all seasons;
- Improved cold start compared to monograde engine oils;
- Low volatility.

QUALITY LEVEL

ISO 6743-15	VOLVO VDS-3
API CI-4/CH-4/CF/SL	Global DHD-1
ACEA E7-12	MACK EO-M Plus /EO-N
MB-Approval 228.3	Renault RLD/RLD-2
MAN M3275	CAT ECF-2, ECF-1-a
MTU Type 2	DEUTZ DQC III-10
Cummins CES 20076/77/78	Detroit Diesel 93K215

APPLICATION

FENIX[®] SUPERIOR PLUS SAE 10W-40 is used for the lubrication of modern four-stroke diesel and gasoline engines of passenger and commercial vehicles, engines for construction, mining and agricultural machines as well as stationary drive units and highly pre-charged engines that work under the most difficult operating conditions. It is suitable for use in EURO III, EURO IV and most EURO V engines without DPF filters.

TYPICAL CHARACTERISTICS

	TYPICAL VALUE	METHOD
Density at 15°C, g/ml	0,87	SRPS EN ISO 3675
Kinematic viscosity at 40°C, mm ² /s	93	SRPS ISO 3104
Kinematic viscosity at 100°C, mm ² /s	14	SRPS ISO 3104
Viscosity index	154	SRPS ISO 2909
Dynamic viscosity at -25°C, mPas	6850	DIN 53018/1
Flash point, °C	225	SRPS EN ISO 2592
Pour point, °C	-33	SRPS ISO 3016
TBN, mg KOH/g	10.5	SRPS ISO 3771
Sulphated ash, %	1,0	SRPS ISO 3987

STORAGE

Store in covered area. If stored outdoors, it is necessary to place the drums in a horizontal position to prevent the accumulation of water on the surface of the drum. Do not store at elevated temperatures or in locations exposed to direct sunlight.

All necessary instructions can be found in the product SDS. It contains the details of possible hazards, warnings and first aid measures, as well as the impact on the environment and the necessary measures for the storage and handling.

PACKING

Drums 175kg, 60L, plastic containers of 1L, 5L, 10L and 20L.

Data are orientational, manufacturer reserves the right to make changes in order to improve product quality.

